



## N100 PORT SYSTEM FOR FUJIFILM X-MOUNT CAMERA SYSTEM

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO APSC	Fujifilm XF 60mm f/2.4 R Macro		36471 N100 to N85 Port Adaptor	37401 N100 Extension Ring 30	37127 N100 Flat Port 32  36135 N85 Flat Port 45			
	Fujifilm XF 80mm f/2.8 R LM OIS WR Macro	36473 X80-F			37125 N100 Macro Port 110	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 1.7X Working Distance 34-93mm
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1  81202 SMC - 2	Max. Magnification 1.7X Working Distance 34-93mm  Max. Magnification 2.5X Working Distance 17-36mm
	Zeiss Touit 50mm f/2.8M			37401 N100 Extension Ring 30	37127 N100 Flat Port 32	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 1.3X Working Distance 17-75mm
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1  81302 CMC - 2	Max. Magnification 1.3X Working Distance 17-75mm  Max. Magnification 1.0X Working Distance 30-130mm
			36471 N100 to N85 Port Adaptor		36135 N85 Flat Port 45	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 1.3X Working Distance 17-75mm
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1  81302 CMC - 2	Max. Magnification 1.3X Working Distance 17-75mm  Max. Magnification 1.0X Working Distance 30-130mm
						<b>83250</b> M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 31° Converted FOV 100°
						SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 1.3X Working Distance 17-75mm
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1  81302 CMC - 2	Max. Magnification 1.3X Working Distance 17-75mm  Max. Magnification 1.0X Working Distance 30-130mm
STANDARD ZOOM APSC	Fujifilm XC 15-45mm f/3.5-5.6 OIS PZ	36476 X1545PZ-Z		36478 N100 Flat Port 40		<b>83250</b> M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	<sup>1</sup> 83201 WWL - 1	Lens FOV 75-35° Converted FOV 130-60° Zoom Range 18-45mm
							83202 WWL - 1B	Lens FOV 75-35° Converted FOV 130-60° Zoom Range 18-45mm
							83203 WWL - C	Lens FOV 39-35° Converted FOV 150-114° Zoom Range 18-45mm
							86201 MWL - 1	Lens FOV 39-35° Converted FOV 150-114° Working Distance 40-45mm

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.  
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APSC - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.  
Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended port system based on best optical performance  
\* Secondary setup recommendation based on optical performance



## N100 PORT SYSTEM FOR FUJIFILM X-MOUNT CAMERA SYSTEM

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
STANDARD ZOOM APSC	Fujifilm XF 18-55mm f/2.8-4 R LM OIS	36474 X1855-Z3	37304 N100 to N120 55mm Port Adaptor	37401 N100 Extension Ring 30	* 85203 N100 WACP-1			Lens FOV 75-52° Converted FOV 130-90° Zoom Range 18-30mm
				37403 N100 Extension Ring 50	* 37129 N100 180mm Optical Glass Wide Angle Port			
WIDE ANGLE APSC	Fujifilm XF 8-16mm f/2.8 R LM WR	36477 X816-Z	37304 N100 to N120 55mm Port Adaptor	21110 Extension Ring 10 with Screws	18809 180mm Optical Glass Wide Angle Port			
				21130 Extension Ring 30 with Lock	* 18812 230mm Optical Glass Wide Angle Port II			
	Fujifilm XF 10-24mm f/4 R OIS WR	36475 X1024-Z	37304 N100 to N120 55mm Port Adaptor	37403 N100 Extension Ring 50	* 37129 N100 180mm Optical Glass Wide Angle Port			
					18809 180mm Optical Glass Wide Angle Port			
Fujifilm XF 18mm f/2 R				36472 N100 Flat Port 13	83250 M67 to Bayonet Mount Converter II	1 83201 WWL - 1	Lens FOV 76.5° Converted FOV 132°	
						83202 WWL - 1B	Lens FOV 76.5° Converted FOV 132°	
Fujifilm XF 23mm f/2 R					37127 N100 Flat Port 32	83250 M67 to Bayonet Mount Converter II	1 83201 WWL - 1	Lens FOV 63.4° Converted FOV 110°
							83202 WWL - 1B	Lens FOV 63.4° Converted FOV 110°

1. We recommend to use #83201 WWL-1 with the pre-installed bayonet mounting ring. #83211 M67 mounting ring (included in WWL-1 package) can also be mounted on the WWL-1 and attach on M67 threaded port directly.  
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APSC - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.  
Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended port system based on best optical performance  
\* Secondary setup recommendation based on optical performance