



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO APS-C	Canon EF-S 60mm f2.8 Macro USM	19521 C60-F	18211 Compact Port Base		18704 Macro Port 41	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81302 CMC - 2	Max. Magnification 1.6X Working Distance 38-120mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2	Max. Magnification 1.6X Working Distance 38-120mm
						81201 SMC - 1	Max. Magnification 1.6X Working Distance 28-94mm	
						81201 SMC - 1	Max. Magnification 1.6X Working Distance 28-94mm	
						83250 M67 to Bayonet Mount Converter II	87302 EMWL Set #2	Lens FOV 24.5° Converted FOV 60°/100°/130°
					18303 Compact Port 15	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81302 CMC - 2	Max. Magnification 1.6X Working Distance 38-120mm
						81201 SMC - 1	Max. Magnification 1.6X Working Distance 28-94mm	
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2	Max. Magnification 1.6X Working Distance 38-120mm
					81201 SMC - 1	Max. Magnification 1.6X Working Distance 28-94mm		
MACRO FULL FRAME	Laowa 24mm f/14 2X Macro Probe	19155 N120 DSLR Gear Set		21271 Extension Ring 70 with Focus Knob	16336 N120 Port Adaptor for Laowa 24mm f/14 2X Macro Probe			
	Canon EF 40mm f2.8 STM <i>* This setup can only be use on APS-C sensor camera</i>				18706 Macro Port 12	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	On APS-C Sensor Lens FOV 37° Converted FOV 135° Working Distance 40mm
	Canon MP-E 65mm f/2.8 1-5x	19539 C65-F	18211 Compact Port Base	18550 Compact Port Extension 50	18306 Compact Port 50 with M67 Thread <i>* magnification 3x</i>			
				18550 + 18530 Compact Port Extension 50 + 30	18306 Compact Port 50 with M67 Thread <i>* magnification 4x</i>			
				18550 + 18530 + 18530 Compact Port Extension 50 + 30 + 30	18306 Compact Port 50 with M67 Thread <i>* magnification 5x</i>			
	Canon EF 100mm f2.8 Macro USM	19522 C100-F				18702 Macro Port 87	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1
81202 SMC - 2							Max. Magnification 4.3X Working Distance 28-38mm	
SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC							81201 SMC - 1	Max. Magnification 2.6X Working Distance 53-93mm
81202 SMC - 2							Max. Magnification 4.3X Working Distance 28-38mm	
					83250 M67 to Bayonet Mount Converter II	87301 EMWL Set #1	Lens FOV 24.0° Converted FOV 60°/100°/130°	

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
MACRO FULL FRAME	Canon EF 100mm f/2.8L Macro IS USM	19523 C100IS-F			18703 Macro Port 94	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 2.2X Working Distance 45-89mm	
							81202 SMC - 2	Max. Magnification 3.6X Working Distance 22-36mm	
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 2.2X Working Distance 45-89mm	
							81202 SMC - 2	Max. Magnification 3.6X Working Distance 22-36mm	
						83250 M67 to Bayonet Mount Converter II	87302 EMWL Set #2	Lens FOV 23.4° Converted FOV 60°/100°/130°	
	Canon EF 180mm f/3.5L Macro USM				21160 Extension Ring 60 with Lock	18703 Macro Port 94	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 3.6X Working Distance 63-92mm
							SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 3.6X Working Distance 63-92mm
	Sigma 50mm F2.8 EX DG Macro			18211 Compact Port Base	18520 Compact Port Extension 20	18303 Compact Port 15			
				18211 Compact Port Base	18530 Compact Port Extension 30	18302 Compact Port 50			
	Sigma 70mm F2.8 EX DG Macro			18211 Compact Port Base	18550 Compact Port Extension 50	18301 Compact Port 30			
18211 Compact Port Base									
Sigma 105mm F2.8 EX DG OS HSM Macro		19553 SC105-F		21130 Extension Ring 30 with Lock	18701 Macro Port 60	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 2.6X Working Distance 50-90mm	
							81202 SMC - 2	Max. Magnification 3.3X Working Distance 31-38mm	
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 2.6X Working Distance 50-90mm	
							81202 SMC - 2	Max. Magnification 3.3X Working Distance 31-38mm	
					83250 M67 to Bayonet Mount Converter II	87301 EMWL Set #1	Lens FOV 24.0° Converted FOV 60°/100°/130°		
STANDARD ZOOM APS-C	Canon EF-S 18-55mm f/3.5-5.6 IS	19532 C1855IS-Z	18211 Compact Port Base		18303 Compact Port 15				
	Canon EF-S 18-55mm f/3.5-5.6 IS STM	19547 C1855ISSTM-Z	18211 Compact Port Base		18303 Compact Port 15				
				21130 Extension Ring 30 with Lock	* 85201 WACP - 1			Lens FOV 75-27.5° Converted FOV 130-46°	
	Canon EF-S 18-135mm f/3.5-5.6 IS	19524 C18135IS-Z		21160 Extension Ring 60 with Lock	18802 8.5" Acrylic Dome Port				
	Sigma 17-70mm F2.8-4.5 DC Macro	19533 SC1770-Z		21150 Extension Ring 50 with Lock	18802 8.5" Acrylic Dome Port				
Sigma 17-70mm F2.8-4 DC Macro OS HSM	19534 SC17700S-Z		21140 Extension Ring 40 with Lock	18802 8.5" Acrylic Dome Port					

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
STANDARD ZOOM APSC	Sigma 18-35mm F1.8 DC HSM A	19552 SC1835f.18-Z			* 85202 WACP-1 for Sigma 18-35mm F1.8		Lens FOV 76.5-44° Converted FOV 132-76°	
					21180 Extension Ring 80 with Lock	18802 8.5" Acrylic Dome Port	* 18809 180mm Optical Glass Wide Angle Port	
						18812 230mm Optical Glass Wide Angle Port II		
					21130 + 21135 Extension Ring 30 with Lock + 35	85201 WACP - 1		Lens FOV 76.5-44° Converted FOV 132-76°
		21150 + 21150 Extension Ring 50 with Lock + 50		18815 250mm Optical Glass Wide Angle Port II				
STANDARD ZOOM FULL FRAME	Canon EF 24mm f/1.4L II USM		21140 Extension Ring 40 with Lock		18802 8.5" Acrylic Dome Port			
	Canon EF 24-70mm f/2.8L II USM	19543 C2470II-Z	21170 Extension Ring 70 with Lock		18802 8.5" Acrylic Dome Port			
	Canon EF 24-70mm f/4L IS USM	19544 C2470f4-Z	21170 Extension Ring 70 with Lock		18802 8.5" Acrylic Dome Port			
	Canon EF 24-105mm f/4L IS USM	19545 C24105-Z	21170 Extension Ring 70 with Lock		18802 8.5" Acrylic Dome Port			
	Canon EF 24-105mm f/4L IS II USM	19562 C24105II-Z	21170 Extension Ring 70 with Lock		18802 8.5" Acrylic Dome Port			
					* 18809 180mm Optical Glass Wide Angle Port			
					18812 230mm Optical Glass Wide Angle Port II			
	Canon EF 28mm f/1.8 USM				85201 WACP - 1		Lens FOV 75° Converted FOV 130°	
	Canon EF 28mm f/2.8 USM				85201 WACP - 1		Lens FOV 75° Converted FOV 130°	
	Canon EF 28-70mm f/3.5-4.5 II	19557 C2870f3.5II-Z	21125 Extension Ring 25 with Lock	* 85201 WACP - 1			Lens FOV 72-34° Converted FOV 130-59°	
	19557 + 19566 C2870f3.5II-Z + C2870f3.5II-F	21130 Extension Ring 30 with Lock	85201 WACP - 1			Lens FOV 72-34° Converted FOV 125-59° Zoom Range 30-70mm		
Canon EF 28-80mm f/3.5-5.6 II	19558 C2880f3.5II-Z	21120 Extension Ring 20 with Lock		18705 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 36-30° Converted FOV 135-113° Working Distance 66-80mm	
		21130 Extension Ring 30 with Lock	* 85201 WACP - 1			Lens FOV 75-30° Converted FOV 130-54°		

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
STANDARD ZOOM FULL FRAME	Canon EF 28-80mm f/3.5-5.6 V USM	19559 C2880f3.5V-Z	21120 Extension Ring 20 with Lock	18705 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 37.5-30° Converted FOV 138-93° Working Distance 63-80mm
			21130 Extension Ring 30 with Lock	* 85201 WACP - 1			Lens FOV 75-31° Converted FOV 130-54°
	Canon EF 35mm f/2 IS USM			85201 WACP - 1			Lens FOV 63° Converted FOV 109°
WIDE ANGLE APS-C	Canon EF-S 10-18mm f/4.5-5.6 IS STM	19549 C1018-Z		* 85204 WACP - 2			Lens FOV 108-75° Converted FOV 128-85°
			21140 Extension Ring 40 with Lock	18809 180mm Optical Glass Wide Angle Port			
			21150 Extension Ring 50 with Lock	18802 8.5" Acrylic Dome Port			
				18809 180mm Optical Glass Wide Angle Port			
				* 18812 230mm Optical Glass Wide Angle Port II			
	Canon EF-S 10-22mm f/3.5-4.5 IS STM	19525 C1022-Z		21110 Extension Ring 10 with Screws	* 85204 WACP - 2		Lens FOV 108-63° Converted FOV 128-85°
				21150 Extension Ring 50 with Lock	18809 180mm Optical Glass Wide Angle Port		
				21160 Extension Ring 60 with Lock	18802 8.5" Acrylic Dome Port		
					18809 180mm Optical Glass Wide Angle Port		
					* 18812 230mm Optical Glass Wide Angle Port II		
	Sigma 8-16mm F4.5-5.6 DC HSM	19536 SC816-Z		21140 Extension Ring 40 with Lock	18809 180mm Optical Glass Wide Angle Port		
				21150 Extension Ring 50 with Lock	18802 8.5" Acrylic Dome Port		
				18812 230mm Optical Glass Wide Angle Port II			
				* 18815 250mm Optical Glass Wide Angle Port II			
Sigma 10-20mm F4.5-5.6 EX DC HSM	19535 SC1020-Z		21140 Extension Ring 40 with Lock	18809 180mm Optical Glass Wide Angle Port			
			21150 Extension Ring 50 with Lock	18802 8.5" Acrylic Dome Port			
				18812 230mm Optical Glass Wide Angle Port II			
				* 18815 250mm Optical Glass Wide Angle Port II			

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE						
WIDE ANGLE APSC	Tokina AT-X 11-20mm F2.8 PRO DX	19573 CT1120-Z	21120 Extension Ring 20 with Lock	* 85204 WACP - 2	Lens FOV 104-72° Converted FOV 123-81°						
				21160 Extension Ring 60 with Lock		18802 8.5" Acrylic Dome Port					
						18809 180mm Optical Glass Wide Angle Port					
						18812 230mm Optical Glass Wide Angle Port II					
						* 18815 250mm Optical Glass Wide Angle Port II					
						Tokina AT-X 116 PRO DX AF 11-16mm f/2.8	19530 TC1116-Z	21110 Extension Ring 10 with Screws	* 85204 WACP - 2	Lens FOV 110-81° Converted FOV 133-93°	
21160 Extension Ring 60 with Lock	18802 8.5" Acrylic Dome Port										
	18809 180mm Optical Glass Wide Angle Port										
	18812 230mm Optical Glass Wide Angle Port II										
	* 18815 250mm Optical Glass Wide Angle Port II										
	Tokina AT-X 124 AF PRO DX AF 12-24mm f/4	19531 TC1224-Z	21150 Extension Ring 50 with Lock	18802 8.5" Acrylic Dome Port							
				21160 Extension Ring 60 with Lock	18809 180mm Optical Glass Wide Angle Port						
18812 230mm Optical Glass Wide Angle Port II											
* 18815 250mm Optical Glass Wide Angle Port II											
Canon EF 11-24mm f/4L USM					19550 C1124-Z	21150 Extension Ring 50 with Lock	* 18815 250mm Optical Glass Wide Angle Port II	* This setup is not compatible with Extension Rings SN:A213191 before 09/2016			
							21170 Extension Ring 70 with Lock	18812 230mm Optical Glass Wide Angle Port II	* This setup is not compatible with Extension Rings SN:A201966 before 09/2016		
	19550 + 19551 C1124-Z + C1124-F	21271 Extension Ring 70 with Focus Knob	18812 230mm Optical Glass Wide Angle Port II								
		Canon EF 16-35mm f/2.8 II USM	19527 C1635II-Z	21130 Extension Ring 30 with Lock				* 85204 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°		
								*Please refer to the following page for more setup options			



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE	
WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/2.8 II USM	19527 C1635II-Z		21170 Extension Ring 70 with Lock	18802 8.5" Acrylic Dome Port	Lens FOV 107-63° Converted FOV 128-72°
				21180 Extension Ring 80 with Lock	18809 180mm Optical Glass Wide Angle Port	
				21182 230mm Optical Glass Wide Angle Port II	* 18815 250mm Optical Glass Wide Angle Port II	
		19527 + 19542 C1635II-Z + C1635II-F		21230 Extension Ring 30 with Focus Knob	* 85204 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°
				21270 Extension Ring 70 with Focus Knob	18802 8.5" Acrylic Dome Port	
	Canon EF 16-35mm f/2.8 III USM	19554 C1635III-Z		21150 Extension Ring 50 with Lock	* 85204 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°
				21170 Extension Ring 70 with Lock	85201 WACP - 1	On APS-C Sensor Lens FOV 80-43° Converted FOV 138-74°
				21180 Extension Ring 80 with Lock	18809 180mm Optical Glass Wide Angle Port	On Full Frame Sensor Lens FOV 75-63° Converted FOV 130-109° Zoom Range 28-35mm
		19554 + 19555 C1635III-Z + C1635III-F		21250 Extension Ring 50 with Focus Knob	85204 WACP - 2	Lens FOV 107-63° Converted FOV 128-72°
				21271 + 21120 Extension Ring 70 with Knob + 20	* 18812 230mm Optical Glass Wide Angle Port II	
Canon EF 16-35mm f/4 IS USM <i>* Please refer to the following page for more setup options</i>	19548 C1635f4-Z		21130 Extension Ring 30 with Lock	* 85204 WACP - 2	Lens FOV 108-63° Converted FOV 128-72°	
			21160 Extension Ring 60 with Lock	85201 WACP - 1	On APS-C Sensor Lens FOV 80-43° Converted FOV 138-74°	
			21170 Extension Ring 70 with Lock	18802 8.5" Acrylic Dome Port	Lens FOV 107-63° Converted FOV 128-72°	
	19548 + 19560 C1635f4-Z + C1635f4-F		21180 Extension Ring 80 with Lock	18809 180mm Optical Glass Wide Angle Port		
			21182 230mm Optical Glass Wide Angle Port II	* 18812 230mm Optical Glass Wide Angle Port II		
			21185 250mm Optical Glass Wide Angle Port II	18815 250mm Optical Glass Wide Angle Port II		
		21271 Extension Ring 70 with Focus Knob	18812 230mm Optical Glass Wide Angle Port II			



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	OPTICAL PERFORMANCE	
WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/4 IS USM	19548 + 19572 C1635f4-Z + WC1635f4-F	21235 Extension Ring 35 with Focus Knob	85204 WACP - 2	Lens FOV 108-63° Converted FOV 128-72°	
	Canon EF 17-40mm f/4L USM	19528 C1740-Z	21140 Extension Ring 40 with Lock	* 85201 WACP - 1	On APS-C Sensor Lens FOV 77-37° Converted FOV 133-74°	
					On Full Frame Sensor Lens FOV 75-57.5° Converted FOV 130-100°	
					18802 8.5" Acrylic Dome Port	
					18809 180mm Optical Glass Wide Angle Port	
	Sigma 12-24mm F4 DG HSM Art	19556 SC1224A-Z	21150 Extension Ring 50 with Lock	18812 230mm Optical Glass Wide Angle Port II	* 18815 250mm Optical Glass Wide Angle Port II	<i>* This setup is not compatible with Extension Rings SN:A213191 before 09/2016</i>
						18815 250mm Optical Glass Wide Angle Port II
						* 18812 230mm Optical Glass Wide Angle Port II
						<i>* This setup is not compatible with Extension Rings SN:A143566 before 09/2016</i>
	Sigma 14mm F1.8 DG HSM Art	19563 SC14A-F	21170 Extension Ring 70 with Lock	18802 8.5" Acrylic Dome Port	* 18812 230mm Optical Glass Wide Angle Port II	<i>* This setup is not compatible with Extension Rings SN:A201966 before 09/2016</i>
<i>* This setup is not compatible with Extension Rings SN:A201966 before 09/2016</i>						
Sigma 14-24mm F2.8 DG HSM Art	19564 SC1424A-Z	21160 Extension Ring 60 with Lock	18809 180mm Optical Glass Wide Angle Port	18802 8.5" Acrylic Dome Port	<i>* This setup is not compatible with Extension Rings SN:A143566 before 09/2016</i>	
					* 18812 230mm Optical Glass Wide Angle Port II	
					18815 250mm Optical Glass Wide Angle Port II	
					<i>* This setup is not compatible with Extension Rings SN:A201966 before 09/2016</i>	
Sigma 20mm F1.4 DG HSM A		21160 Extension Ring 60 with Lock	18809 180mm Optical Glass Wide Angle Port	18802 8.5" Acrylic Dome Port	<i>* This setup is not compatible with Extension Rings SN:A201966 before 09/2016</i>	
					* 18812 230mm Optical Glass Wide Angle Port II	
					18815 250mm Optical Glass Wide Angle Port II	
					<i>* This setup is not compatible with Extension Rings SN:A201966 before 09/2016</i>	



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	
WIDE ANGLE FULL FRAME	ZEISS Distagon T* 15mm f/2.8 ZM	16319 ZC15-F	21155 Extension Ring 55 with Lock	18812 230mm Optical Glass Wide Angle Port II	<i>* This setup is not compatible with Extension Rings SN:A055053 before 09/2016</i>
	ZEISS Milvus 18mm f/2.8 ZE	16329 ZMC-F	21150 Extension Ring 50 with Lock	18809 180mm Optical Glass Wide Angle Port * 18812 230mm Optical Glass Wide Angle Port II	
	ZEISS Milvus 21mm f/2.8 ZE	16329 ZMC-F	21150 Extension Ring 50 with Lock	18809 180mm Optical Glass Wide Angle Port * 18812 230mm Optical Glass Wide Angle Port II	
FISHEYE APSC	Sigma 10mm F2.8 EX DC HSM Fisheye		21110 Extension Ring 10 with Screws	18802 8.5" Acrylic Dome Port	
	Tokina AT-X 107 AF DX Fisheye AF 10-17mm f/3.5-4.5	19529 TC1017-Z	21110 Extension Ring 10 with Screws	18804 4.33" Acrylic Dome Port for Tokina 10-17mm * 18810 140mm Optical Glass Fisheye Port	
			21120 Extension Ring 20 with Lock	18802 8.5" Acrylic Dome Port 18812 230mm Optical Glass Wide Angle Port II	
	Tokina AT-X 107 AF DX Fisheye AF 10-17mm f/3.5-4.5 with Kenko TELEPLUS HD pro 1.4x DGX Teleconverter for Canon EF	19629 TC1017-Z + 1.4X	21120 Extension Ring 20 with Lock 21130 Extension Ring 30 with Lock 21140 Extension Ring 40 with Lock	18804 4.33" Acrylic Dome Port for Tokina 10-17mm * 18810 140mm Optical Glass Fisheye Port 18802 8.5" Acrylic Dome Port 18812 230mm Optical Glass Wide Angle Port II	
FISHEYE FULL FRAME	Canon EF 8-15mm f/4L Fisheye USM	19537 C815-Z	21130 Extension Ring 30 with Lock	18802 8.5" Acrylic Dome Port * 18811 140mm Optical Glass Fisheye Port with Removable Shade 18812 230mm Optical Glass Wide Angle Port II	
		19537 + 19541 C815-Z + C815-F	21230 Extension Ring 30 with Focus Knob	18802 8.5" Acrylic Dome Port	



N120 PORT SYSTEM FOR CANON EF-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT
FISHEYE FULL FRAME	Canon EF 8-15mm f/4L Fisheye USM with Kenko 1.4x Teleplus Pro 300 DGX	19538 C815-Z + 1.4X	21150 Extension Ring 50 with Lock	18802 8.5" Acrylic Dome Port * 18811 140mm Optical Glass Fisheye Port with Removable Shade 18812 230mm Optical Glass Wide Angle Port II
	Canon EF 15mm f/2.8 Fisheye		21110 Extension Ring 10 with Screws	18802 8.5" Acrylic Dome Port * 18812 230mm Optical Glass Wide Angle Port II
	Sigma 15mm F2.8 EX DG Diagonal Fisheye	19546 SC15-F		18802 8.5" Acrylic Dome Port * 18810 140mm Optical Glass Fisheye Port 18812 230mm Optical Glass Wide Angle Port II