



N85 PORT SYSTEM FOR CANON EF-M-MOUNT CAMERA SYSTEM (APS-C Format Lens)

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE				
MACRO APS-C	Canon EF-S 60mm f/2.8 Macro USM with Canon EF-M Lens Adapter Kit	36192 CMEF60-F 19521 C60-F			36182 Macro Port for Canon EF-EOS M Adaptor 18704 Macro Port 41	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81302 CMC - 2 81201 SMC - 1	Max. Magnification 1.6X Working Distance 38-120mm Max. Magnification 1.6X Working Distance 28-94mm				
						SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81302 CMC - 2 81201 SMC - 1	Max. Magnification 1.6X Working Distance 38-120mm Max. Magnification 1.6X Working Distance 28-94mm				
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2 81201 SMC - 1	Max. Magnification 1.6X Working Distance 38-120mm Max. Magnification 1.6X Working Distance 28-94mm				
STANDARD ZOOM APS-C	Canon EF-M 15-45mm f/3.5-6.3 IS STM	36195 CM1545-Z			36135 N85 Macro Port 45	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1 81302 CMC - 2	Max. Magnification 0.8X Working Distance 37-81mm Max. Magnification 0.7X Working Distance 59-150mm				
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1 81302 CMC - 2	Max. Magnification 0.8X Working Distance 37-81mm Max. Magnification 0.7X Working Distance 59-150mm				
						83250 M67 to Bayonet Mount Converter II	¹ 83201 WWL - 1 83202 WWL - 1B 83203 WWL - C	Lens FOV 74-33° Converted FOV 128-57° Zoom Range 18-45mm Lens FOV 74-33° Converted FOV 128-57° Zoom Range 18-45mm Lens FOV 76-33° Converted FOV 117-51° Zoom Range 17-45mm				
	Canon EF-M 18-55mm f/3.5-5.6 IS STM	36191 CM1855-Z			36181 4" Acrylic Wide Angle Port	25105 + 81222 M67 Flip Diopter Holder for 36137 + M67 Adapter Ring	81302 CMC - 1	Max. Magnification 0.6X Working Distance 58-127mm				
									36131 3.5" Acrylic Wide Angle Port	83250 M67 to Bayonet Mount Converter II	¹ 83201 WWL - 1 83202 WWL - 1B	Lens FOV 63° Converted FOV 109°
Canon EF-M 22mm f/2 STM				36131 3.5" Acrylic Wide Angle Port	83250 M67 to Bayonet Mount Converter II	¹ 83201 WWL - 1 83202 WWL - 1B	Lens FOV 63° Converted FOV 109°					
WIDE ANGLE APS-C	Canon EF-M 11-22mm f/4-5.6 IS STM	36194 CM1122-Z			36181 4" Acrylic Wide Angle Port 36133 6" Acrylic Wide Angle Port 36129 7" Acrylic Dome Port	18809 180mm Optical Glass Wide Angle Port						
									36204 N85 to N120 60mm Port Adaptor	¹ 83201 WWL - 1 83202 WWL - 1B	Lens FOV 63° Converted FOV 109°	

1. #36184 & Port Adaptor is incompatible to used on NA-EOSM & NA-EOSM3 housings
 Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.
 Working distance operates from the distance between the subject and the front element of the close-up lens.

¹ Recommended port system based on best optical performance
 * Secondary setup recommendation based on optical performance



N85 PORT SYSTEM FOR CANON EF-M-MOUNT CAMERA SYSTEM (Full Frame Format Lens with Canon EF-M Lens Adapter Kit)

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE		
CANON EF-MOUNT	Canon EF 8-15mm f/4L Fisheye USM with Canon EF-M Lens Adapter Kit	36193 CMEF815-Z				36183 4.33" Acrylic Dome Port for Canon EF 8-15mm f/4L Fisheye USM				
		19537 C815-Z	¹ 36184 N85 to N120 41.5mm Port Adaptor	21130 Extension Ring 30 with Lock	* 18811 140mm Optical Glass Fisheye Port with Removable Shade					
	Canon EF 100mm f/2.8L Macro IS USM with Canon EF-M Lens Adapter Kit			36204 N85 to N120 60mm Port Adaptor	21130 Extension Ring 30 with Lock	18704 Macro Port 41	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 2.0X Working Distance 45-95mm	
								81202 SMC - 2	Max. Magnification 3.4X Working Distance 23-39mm	
								81302 CMC - 2	Max. Magnification 2.1X Working Distance 53-127mm	
								SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 2.0X Working Distance 45-95mm
									81202 SMC - 2	Max. Magnification 3.4X Working Distance 23-39mm
									81302 CMC - 2	Max. Magnification 2.1X Working Distance 53-127mm
	Other Canon EF-mount Lenses with Canon EF-M Lens Adapter Kit			19523 C100IS-F	¹ 36184 N85 to N120 41.5mm Port Adaptor	18703 Macro Port 94	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 2.0X Working Distance 45-95mm	
								81202 SMC - 2	Max. Magnification 3.4X Working Distance 23-39mm	
						81302 CMC - 2		Max. Magnification 2.1X Working Distance 53-127mm		
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 2.0X Working Distance 45-95mm		
							81202 SMC - 2	Max. Magnification 3.4X Working Distance 23-39mm		
							81302 CMC - 2	Max. Magnification 2.1X Working Distance 53-127mm		

1. #36184 & Port Adaptor is incompatible to used on NA-EOSM & NA-EOSM3 housings

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance

* Secondary setup recommendation based on optical performance