



DLMPort System Charts for Canon RF Mount

PORT OPTIONS

Some lenses have more than one port option. The first column is always the recommended option for the best compromise of imaging quality, performance, and handling with any given lens.

PRODUCT(S) REQUIRED

Where multiple lines of products are listed for a given option, all products listed are required to make a complete compatible lens port.

The DLM 8" Dome Port # 5516.82 may be substituted with the Modular 8" Dome for FL Systems # 5510.45 + DLM Adapter for Modular 8" Dome # 5516.80 in all instances.

LENSES REFERENCING "+4 DIOPTRER REQUIRED"

A +4 diopter is available for purchase through your local camera store, and is commonly sold in a set with +1 and +2 close-up lenses. Common brands include Tiffen and Hoya. Make sure to purchase the correct size for your lens. The thread diameter is usually referenced on the front of the lens in millimeters (\emptyset 58mm, 67mm, etc.). All photos will be out of focus if a +4 diopter is required but not used.

Canon RF Lenses

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
8-15 mm Canon EF f/4L Fisheye USM + Canon EF-to-RF Adapter	<p>The only port option that supports zoom. AF Only.</p> <p>Product(s) required</p> <p>5516.16 Dome Port 5515.12 Zoom Gear</p>	<p>Zoom not supported. Lens must be used at a fixed focal length. AF Only.</p> <p>Product(s) required</p> <p>5516.82 Dome Port</p>	
10-17 mm Tokina AT-X f/3.5-4.5 DX Fish-eye + Canon EF-to-RF Adapter	<p>Use zoom clamp without foam strips. AF Only.</p> <p>Product(s) required</p> <p>5516.15 Dome Port 5509.30 Zoom Gear</p>		
14-35 mm Canon RF f/4L IS USM	<p>AF Only.</p> <p>Product(s) required</p> <p>5516.17 Dome Port 5515.19 Zoom Gear</p> <p>Optional accessories:</p> <p>0923.14 Anti-Reflection Ring</p>	<p>Zoom not supported. Lens must be used at a fixed focal length. AF Only.</p> <p>Product(s) required</p> <p>5516.82 Dome Port 5516.67 Extension</p> <p>Optional accessories:</p> <p>0923.14 Anti-Reflection Ring</p>	
15-30 mm Canon RF f/4.5-6.3 IS STM	<p>AF Only.</p> <p>Product(s) required</p> <p>5516.17 Dome Port 5509.31 Zoom Gear</p> <p>Optional accessories:</p> <p>0923.15 Anti-Reflection Ring</p>		
15-35 mm Canon RF f/2.8L	<p>This lens is too large in diameter for the DLM port system.</p>		
16 mm Canon RF f/2.8 STM	<p>AF Only.</p> <p>Product(s) required</p> <p>5516.11 Dome Port</p>		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
18-35 mm Sigma f/1.8 DC HSM Art	AF Only. <u>Product(s) required</u> 5516.17 Dome Port 5516.69 Extension 5515.62 Zoom Gear		
18-45 mm Canon RF-S f/4.5-6.3 IS STM	AF Only. <u>Product(s) required</u> 5516.15 Dome Port 5515.14 Zoom Gear <u>Optional accessories:</u> 0923.16 Anti-Reflection Ring		
18-150 mm Canon RF-S f/3.5-6.3 IS STM	Superior edge sharpness compared to shorter port options. AF Only. <u>Product(s) required</u> +4 Diopter Required 5516.16 Dome Port 5516.65 Extension 5515.16 Zoom Gear <u>Optional accessories:</u> 0923.17 Anti-Reflection Ring	A longer port is recommended for better edge sharpness. AF Only. <u>Product(s) required</u> +4 Diopter Required 5516.15 Dome Port 5516.65 Extension 5515.16 Zoom Gear <u>Optional accessories:</u> 0923.17 Anti-Reflection Ring	Zoom not supported. Lens must be used at a fixed focal length. AF Only. <u>Product(s) required</u> +4 Diopter Required 5516.82 Dome Port 5516.65 Extension 5515.16 Zoom Gear <u>Optional accessories:</u> 0923.17 Anti-Reflection Ring
24 mm Canon RF f/1.8 Macro IS STM	AF Only. <u>Product(s) required</u> 5516.12 Dome Port	AF Only. <u>Product(s) required</u> 5516.11 Dome Port	
60 mm Canon EF-S f/2.8 Macro USM + Canon EF-to-RF Adapter	AF Only. <u>Product(s) required</u> 5516.45 Flat Port 5516.65 Extension		
85 mm Canon RF Macro	AF Only. <u>Product(s) required</u> 5516.50 Flat Port 5516.65 Extension		
100 mm Canon RF Macro IS USM	AF Only. <u>Product(s) required</u> 5516.51 Flat Port 5516.70 Extension	AF Only. <u>Product(s) required</u> 5516.50 Flat Port (2) 5516.65 Extension	

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
100 mm Canon EF f/2.8L Macro IS USM + Canon EF-to-RF Adapter	AF Only. <u>Product(s) required</u> 5516.51 Flat Port 5516.70 Extension	AF Only. <u>Product(s) required</u> 5516.50 Flat Port (2) 5516.65 Extension	